

TECHNICAL CHARACTERISTICS SHEET

REFERENCE	75x75 ART
	DRY PRESSED GLAZED FLOOR TILE
	GROUP: Bib

TESTS PERFORMED	RESULTS
UNE-EN ISO 10545-2 DIMENSIONS AND SURFACE QUALITY	CONFORMS TO STANDARD
UNE-EN ISO 10545-3 WATER ABSORPTION $0,5 < E \leq 3\%$	AVERAGE VALUE 0,9%
UNE-EN ISO 10545-4 MODULUS OF RUPTURE	MODULUS OF RUPTURE (N/mm ²) 38 BREAKING STRENGTH (N) 1815
UNE-EN ISO 10545-7 RESISTANCE TO SURFACE ABRASION PEI	CLASS 4
UNE-EN ISO 10545-8 LINEAR THERMAL EXPANSION	$6,3 \times 10^{-5}/^{\circ}\text{C}$
UNE-EN ISO 10545-9 THERMAL SHOCK	RESIST
UNE-EN ISO 10545-11 CRAZING RESISTANCE	FREE OF CRAZES
UNE-EN ISO 10545-12 FROST RESISTANCE	RESIST
UNE-EN ISO 10545-13 CHEMICAL RESISTANCE	AMMONIUM CHLORIDE A SODIUM HYPOCHLORITE A ACIDS AND ALKALIS LA
UNE-EN ISO 10545-14 RESISTANCE TO STAINS	GREEN STAINING AGENT IN LIGHT OIL CLASS 5 IODINE ALCOHOL SOLUTION CLASS 5 OLIVE OIL CLASS 5

Date. 19/08/19



Cerpa, S.L.